

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)

PH	DE	MAT.
000137 WO PCT DOSSIER		

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : A61B 6/00	A1	(11) International Publication Number: WO 00/24314
		(43) International Publication Date: 4 May 2000 (04.05.00)
(21) International Application Number: PCT/EP99/07469 (22) International Filing Date: 29 September 1999 (29.09.99) (30) Priority Data: 98203555.2 23 October 1998 (23.10.98) EP (71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (72) Inventor: VAN DER ENDE, Adrianus; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). (74) Agent: BAKKER, Hendrik; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).		(81) Designated States: JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: TOMOGRAPHY DEVICE

(57) Abstract

A tomography device (1), which includes a frame (2), a table (10) for supporting a patient (11) to be examined, an X-ray source (6) which is pivotable about a pivot shaft (8) in order to direct the X-ray towards the table during operation, and a receiving plate (5) which is displaceable relative to the frame (2) in order to pick up X-rays emitted by the X-ray source (6) during operation. The pivot shaft (8) is journaled in a slide (3) which is displaceable relative to the frame (2) by means of a guide system. The slide (3) also accommodates the receiving plate (5).



THIS PAGE BLANK (USPTO)

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

TOMOGRAPHY DEVICE

The invention relates to a tomography device which includes a frame, a table for supporting a patient to be examined, an X-ray source which is pivotable about a pivot shaft in order to direct the X-rays towards the table during operation, and a receiving plate which is displaceable relative to the frame in order to receive the X-rays emitted by the X-ray source during operation.

The invention also relates to a method which is suitable for forming a tomographic image by means of such a tomography device.

In a device and a method of this kind which are known from international patent application WO 88/08277, the X-ray source is pivotable about a pivot shaft which is connected to the frame. A housing accommodating the receiving plate is connected to the pivot shaft. The receiving plate is displaceable relative to the housing via a guide system. The patient table is arranged on the housing. The patient table can be displaced relative to the housing by means of a second guide system.

The patient to be examined is arranged on the patient table in order to form a tomographic image. Subsequently, the patient table is displaced relative to the housing, by way of the second guide system, until the part of the patient to be examined is situated over the receiving plate. During the formation of the tomographic image, the X-ray source is pivoted about the pivot shaft and at the same time the receiving plate is displaced relative to the patient by means of the first guide system. A tomographic image of a desired plane within the patient is formed in dependence on the relative speeds and displacements of the X-ray source and the receiving plate.

It is a drawback of the known device that it requires two guide systems; this makes the device comparatively complex.

It is an object of the invention to provide a tomography device having a simpler construction.

This object is achieved for the tomography device according to the invention in that the pivot shaft is journaled in a slide which is displaceable relative to the frame by way of a guide system, the slide also accommodating the receiving plate.

Via the slide which is slidable on the guide system, the X-ray source and the receiving plate can be displaced together relative to the patient table, so that the X-ray source and the receiving plate can be positioned near the part of the patient to be examined. Moreover, during the formation of the tomographic image the receiving plate is displaced
5 relative to the patient by means of the slide. Thus, only a single guide system is required. This allows for a comparatively compact construction of the tomography device.

An embodiment of the tomography device according to the invention is characterized in that the center line of the pivot shaft, extending parallel to the receiving plate, also extends through the receiving plate.

10 Because the center line of the pivot shaft is situated in the same plane as the receiving plate, it is comparatively easy to determine which pivoting motions must be performed by the X-ray source and which displacements must be performed by the slide in order to obtain a tomographic image of a desired plane within the patient.

A further embodiment of the tomography device according to the invention is
15 characterized in that the device includes a controller for controlling the pivoting of the X-ray source and the displacement of the slide during operation.

The controller controls the pivoting motions of the X-ray source and the displacements of the slide in such a manner that a tomographic image can be formed of a desired plane within the patient.

20 The invention will be described in detail hereinafter with reference to the drawings; therein:

Fig. 1 is a side elevation of a first embodiment of a tomography device according to the invention,

Fig. 2 is a side elevation of a second embodiment of a tomography device
25 according to the invention,

Fig. 3 is a rear view of the tomography device shown in Fig. 2, and

Fig. 4 is a perspective view of the tomography device shown in Fig. 2, and

Fig. 5 is a side elevation, representing different operating positions, of a part of the tomography devices shown in the Figs. 1 and 2.

30 Corresponding components are denoted by the same reference numerals in the Figures.

Fig. 1 shows a tomography device 1 according to the invention which includes a frame 2, a slide 3 which is displaceable relative to the frame 2, a cassette or image intensifier 4 which is connected to the slide 3 and accommodates a receiving plate 5, and an X-ray source

6 which is connected to the slide 3, by way of an arm 7, so as to be pivotable about a pivot shaft 8. The center line 9 of the pivot shaft 8 extends parallel to the receiving plate 5 and through the receiving plate 5. The tomography device 1 also includes a patient table 10 for accommodating a patient 11.

5 The frame 2 is provided with an endless chain 12 which is guided on two sprockets 13. One sprocket 13 can be rotated by means of a motor 14. The chain 12 is connected to the slide 3. The slide 3 is provided with casters 15 which bear on the frame 2. When the sprocket 13 is driven by means of the motor 14, the chain 12, and hence the slide 13 connected thereto, is displaced in the direction indicated by the arrow P or in the opposite
10 direction. The slide 3 is also provided with a journal for the pivot shaft 8. The arm 7, connected to the pivot shaft 8, is provided with an arc-shaped rack 16. The rack 16 has a radius whose center is coincident with the center line 9. The slide 3 is also provided with a pinion 17 which engages the rack 16. The pinion 17 is rotatable by means of a motor 18. When the pinion 17 is driven by means of the motor 18, the rack 16, and hence the arm 7 and
15 the X-ray source 6 connected thereto, is pivoted in the direction indicated by the arrow R or in the opposite direction.

 The operation of the tomography device 1 will be described in detail with reference to Fig. 5.

 The Figs. 2 to 4 show a second embodiment of a tomography device 20
20 according to the invention which essentially corresponds to the tomography device 1 shown in Fig. 1. In the tomography device 20 shown in the Figs. 2 to 4, however, the X-ray source 6 is pivoted about the center line 9 in a different manner in comparison with the tomography device 1 shown in Fig. 1. The arm 7 in the tomography device 20 is provided with an elongate slot 21 which is engaged by a pin 22. The pin 22 is connected to a wheel 24 which is rotatable
25 about a shaft 23. The shaft 23 is rotatably journaled in the slide 3. The tomography device 20 also includes a pinion 17 which is rotatable by means of a motor 18. An endless belt 25 is guided on the pinion 17 and the wheel 24. When the pinion 17 is rotated, the wheel 24 is rotated about the shaft 23 together with the pin 22. The pin 22 then pivots the arm 7 about the center line 9; the pin 22 is then displaced in the slot 21. The ends of the slot 21 define the
30 extreme positions of the arm 7 and hence of the X-ray source 6.

 The operation of the tomography device 20 and the tomography device 1 shown in Fig. 1 will now be described in detail with reference to Fig. 5. After a patient 11 has been arranged on the patient table 10, the slide 3 is displaced in the direction denoted by the arrow B1, or in the opposite direction, until the X-ray source 6, connected to the slide 3, and the

receiving plate 5, arranged in the cassette or image intensifier 4, are situated near the part of the patient 11 for which a tomographic image is to be formed. Subsequently, the slide is displaced, together with the receiving plate 5 and the X-ray source 6 connected thereto, in the direction indicated by the arrow P. At the same time the X-ray source 6 is pivoted about the pivot shaft 8 in a direction which opposes that of the arrow R. The X-ray source successively occupies the positions denoted by the references 6'', 6 and 6' whereas the member 4 successively occupies the positions denoted by the references 4'', 4 and 4'. A central X-ray 26 emitted by the X-ray source 6 passes through a point M within the patient in any position of the X-ray source 6 and the slide 3. The point M is situated in a plane 27 for which the tomographic image is to be formed. As a result of the displacement of the X-ray source 6 and the receiving plate 5 relative to one another, a focused image is obtained only of the plane 27. In the situation shown in Fig. 5, the plane 27 is situated at a distance H from the patient table 10. A tomographic image of a plane 27 situated at any desired distance H from the patient table 10 can be obtained by controlling the speed and the displacement of the slide 3 and the rotary speed and pivoting motion of the X-ray source 6 by means of a controller.

The patient table 10 may be rigidly connected to the frame 2. It is alternatively possible to connect the patient table 10 to the frame so as to be tiltable, for example as described in the cited international patent application WO 88/08277 or in WO 97/10750.

It is alternatively possible to displace the slide 3 relative to the frame 2 by means of a different drive, for example a spindle or a toothed belt.

It is also possible for the receiving plate to form part of an X-ray image intensifier, a semiconductor X-ray detector or another X-ray detector.

CLAIMS:

1. A tomography device, which includes a frame, a table for supporting a patient to be examined, an X-ray source which is pivotable about a pivot shaft in order to direct the X-rays towards the table during operation, and a receiving plate which is displaceable relative to the frame in order to receive the X-rays emitted by the X-ray source during operation,
5 characterized in that the pivot shaft is journaled in a slide which is displaceable relative to the frame by way of a guide system, the slide also accommodating the receiving plate.
2. A tomography device as claimed in Claim 1, characterized in that the center
10 line of the pivot shaft, extending parallel to the receiving plate, also extends through the receiving plate.
3. A tomography device, characterized in that the device includes a controller for
controlling the pivoting of the X-ray source and the displacement of the slide during operation.
- 15 4. A method suitable for forming a tomographic image by means of the tomography device as claimed in one of the preceding Claims, characterized in that a controller is used to control the pivoting motion of the X-ray source and the displacement of the slide in such a manner that a tomographic image of a predetermined plane within the patient is formed.

1/5




FIG. 1

2/5




FIG. 2

3/5




FIG. 3

4/5




FIG. 4

5/5




FIG. 5

INTERNATIONAL SEARCH REPORT

Int. .onal Application No

PCT/EP 99/07469

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B6/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 086 448 A (MUTHMANN KARL-DIETER) 4 February 1992 (1992-02-04) column 1, line 59 -column 3, line 3; figure 1	1-4
X	US 5 095 501 A (KOBAYASHI TOHRU) 10 March 1992 (1992-03-10) column 4, line 29 -column 5, line 8; figure 3	1,2,4
A		3
X	WO 98 24368 A (PHILIPS ELECTRONICS NV) 11 June 1998 (1998-06-11) page 4, line 26 -page 5, line 16; figure 1	1,2,4

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

24 January 2000

Date of mailing of the international search report

31/01/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Martelli, L

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/07469

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5086448	A	04-02-1992	NONE	
US 5095501	A	10-03-1992	JP 3176033 A	31-07-1991
WO 9824368	A	11-06-1998	CN 1215315 A	28-04-1999
			EP 0897286 A	24-02-1999